

LSF 001 - LSF 095 metrisch

Maschine							
Typ		LSF001	LSF004	LSF006	LSF016	LSF035	LSF095
Schweißbereich Litzen							
Kupfer	mm ²	0,12 - 1,0	0,2 - 4,0	0,75 - 6,0	1,0 - 16	4,0 - 35	6,0 - 95
Aluminium	mm ²		0,5 - 4,0	1,0 - 6,0	2,5 - 16	10 - 50	16 - 95
Spannsystem							
Stauchkraft	N	8,3	8,3	18	40	850	850
Leistung							
Nennleistung (50% ED)	kVA	0,42	0,42	0,42	2,1	8,0	25,0
Maße und Gewicht							
B x T x H	mm	485 x 550 x 1050	485 x 550 x 1050	485 x 550 x 1050	765 x 735 x 1315	800 x 590 x 1300	800 x 590 x 1300
Gewicht	kg	46	41,5	41,5	105	210	215

LSF 001 - LSF 095 imperial

Maschine							
Typ		LSF001	LSF004	LSF006	LSF016	LSF035	LSF095
Schweißbereich Litzen							
Kupfer	AWG	26 - 18	24 - 12	19 - 10	18 - 6	12 - 2	10 - 3/0
Aluminium	AWG		20 - 12	18 - 10	14 - 6	8 - 1/0	6 - 3/0
Spannsystem							
Stauchkraft	lbf	1,9	1,9	4,0	9,0	191	191
Leistung							
Nennleistung (50% ED)	kVA	0,42	0,42	0,42	2,1	8,0	25,0
Maße und Gewicht							
B x T x H	inch	19,1 x 21,7 x 41,3	19,1 x 21,7 x 41,3	19,1 x 21,7 x 41,3	30,1 x 28,9 x 51,8	31,5 x 23,2 x 51,2	31,5 x 23,2 x 51,2
Gewicht	lb	101	91	91	231	463	474

LSH 004 - LSH 095 metrisch

Maschine						
Typ		LSH004	LSH006	LSH016	LSH035	LSH095
Schweißbereich Litzen						
Kupfer	mm ²	0,2 - 4,0	0,75 - 6,0	1,0 - 16	4,0 - 35	6,0 - 95
Aluminium	mm ²	0,5 - 4,0	1,0 - 6,0	2,5 - 16	10 - 50	16 - 95
Spannsystem						
Stauchkraft	N	8,3	18	40	850	850
Leistung						
Nennleistung (50% ED)	kVA	0,42	0,42	2,1	8	25
Maße und Gewicht						
B x T x H	mm	370 x 290 x 250	370 x 290 x 250	480 x 410 x 560	800 x 590 x 1420	800 x 590 x 1420
Gewicht	kg	17,5	17,5	75	192	198

LSH 004 - LSH 095 imperial

Maschine						
Typ		LSH004	LSH006	LSH016	LSH035	LSH095
Schweißbereich Litzen						
Kupfer	AWG	24 - 12	19 - 10	18 - 6	12 - 2	10 - 3/0
Aluminium	AWG	20 - 12	18 - 10	14 - 6	8 - 1/0	6 - 3/0
Spannsystem						
Stauchkraft	lbf	1,9	4,0	9,0	191	191
Leistung						
Nennleistung (50% ED)	kVA	0,42	0,42	2,1	8	25
Maße und Gewicht						
B x T x H	inch	14,6 x 11,4 x 9,8	14,6 x 11,4 x 9,8	18,9 x 16,1 x 22,0	31,5 x 23,2 x 55,9	31,5 x 23,2 x 55,9
Gewicht	lb	39	39	165	423	437

LS0 185 - LS0 630 metrisch

Maschine					
Typ		LS0 185	LS0300	LS0400	LS0630
Schweißbereich Litzen					
Kupfer	mm ²	16 - 185	25 - 300	35 - 400	50 - 630
Aluminium	mm ²	25 - 240	35 - 400	50 - 500	70 - 800
Spannsystem					
Stauchkraft	kN	3,5	3,5	3,5	3
Leistung					
Nennleistung (50% ED)	kVA	70	70	120	120
Maße und Gewicht					
B x T x H	mm	1345 x 800 x 1475	1345 x 800 x 1475	1345 x 800 x 1475	1345 x 800 x 1475
Gewicht	kg	650	650	850	850

LS0 185 - LS0 630 imperial

Maschine					
Typ		LS0 185	LS0300	LS0400	LS0630
Schweißbereich Litzen					
Kupfer	AWG	6 - 350 MCM	4 - 600 MCM	2 - 750 MCM	1/0 - 1250 MCM
Aluminium	AWG	4 - 500 MCM	2 - 750 MCM	1/0 - 1000 MCM	2/0 - 1575 MCM
Spannsystem					
Stauchkraft	lbf	787	787	787	674
Leistung					
Nennleistung (50% ED)	kVA	70	70	120	120
Maße und Gewicht					
B x T x H	inch	53,0 x 31,5 x 58,1	53,0 x 31,5 x 58,1	53,0 x 31,5 x 58,1	53,0 x 31,5 x 58,1
Gewicht	lb	1433	1433	1874	1874